


WWW.PRG.COM

BEST BOY® HP SPOT LUMINAIRE PHOTOMETRICS

REFERENCE GUIDE






Throw Dist. (Ft)	20	30	50	75	100
Beam Dia. (Ft)	2.4	3.7	6.1	9.2	12.2
Illuminance (fc)	6510	2893	1042	463	260
Throw Dist. (m)	5	10	20	25	30
	5 0.6	10 1.2	20 2.4		30 3.7

Multiply throw distance by Tn to find beam diameter.

Divide cd (candela) by distance squared to find center beam illuminance.

Distance in feet = foot candles

Distance in meters = lux





Iris Full Open 39° Full Angle 32,000 Total Lumens


Throw Dist. (Ft)	20	30	50	75	100
Beam Dia. (Ft)	12.2	18.3	30.6	45.8	61.1
Illuminance (fc)	333	148	53	24	13
Throw Dist. (m)	5	10	20	25	30
Beam Dia. (m)	3.1	6.1	12.2	15.3	18.3
Illuminance (lux)	5328	1332	333	213	148

Multiply throw distance by Tn to find beam diameter.

Divide cd (candela) by distance squared to find center beam illuminance.

Distance in feet = foot candles

Distance in meters = lux







Throw Dist. (Ft)	20	30	50	75	100
Beam Dia. (Ft)	17.8	26.7	44.5	66.8	89.0
Illuminance (fc)	122	54	20	9	5
Throw Dist. (m)	5	10	20	25	30
Beam Dia. (m)	4.5	8.9	17.8	22.3	26.7
Illuminance (lux)	1952	488	122	78	54

Multiply throw distance by Tn to find beam diameter.

Divide cd (candela) by distance squared to find center beam illuminance.

Distance in feet = foot candles

Distance in meters = lux

