

ICON STAGE

Icon Stage is the latest fixture in the Icon range. Featuring a high output LED engine, Icon Stage outputs a blinding 14,000 lumens at a colour temperature of 7,500k.

Full of features you would expect including 8-56° zoom optics, full CMY Colour mixing alongside a fixed colour wheel and variable CTO. 8 fixed gobos and 7 rotating give the fixture class leading functionality, coupled with full framing shutters, iris and prism functions and dual drop in frosts the Icon Stage is truly in a class of its own.

Icon Stage is whisper quiet during operation. Direct Art-Net input and DMX512 is available for control of the fixture.



Features:

| | | | |
|------------------|--------------------------|---------------------------|-------------------------------|
| Source | 420W White LED | Animation Wheel* | Continuous Rotation |
| Brightness | 14,000 Lumen | Strobe/Shutter | Electronic, 13 Flash/sec |
| Colour Temp | 7,500K | Dimmer | 5 dimming curves, 16Bit |
| CRI | >90 @ 10,000 Lumen | Pan/Tilt | 540/270° |
| | 75 @ 14,000 Lumen | DMX Control Mode | 2 modes |
| Optics/Zoom | 8°-56° | RDM | Yes |
| Frost | 2x drop in frost | Art-NET | Yes |
| CMY | Variable CMY | Cooling System Monitoring | Yes |
| CTO | Variable CTO | Wattage | 536W |
| Colour Wheel | 7+open (interchangeable) | Power | AC100-240V, 50/60Hz |
| Rotating Gobo* | 7+open (interchangeable) | | powerCON TRUE1 & pass through |
| Fixed Gobo | 8+open (interchangeable) | Operating Temperature | -10° to 45° C |
| Iris | Yes | Certification | CE & cETL |
| Framing | 4 frames | Weight | 29kg |
| Framing Rotation | +/- 45°, 90° total | Dimensions LxWxH (mm): | 453x393x720 |
| Prism (Indexing) | 5 Facet | *Indexing | |

